



Specifications

Model Numbers

IDVR1007	9-Channel Network Digital Video Recorder, Refresh rate of 120 images per second for NTSC and 100 images per second for PAL
----------	--

Electrical

Input Power	AC 100 ~ 240 +/- 10% switching adaptor
Power Consumption	<32 Watts

Environmental

Operating temperature	10 ° C to 40 ° C
Storage temperature	0 ° C to 45 ° C
Humidity	85% RH (non-condensing)

Operational

Video format	NTSC/EIA or PAL/CCIR
Refresh Rate	120 images/sec. <NTSC> / 100 images/sec. <PAL>
Hard disk storage	IDE type, UDMA 66, supported over 250 GB HDD
Recording mode	Manual / Alarm / Timer / Motion
Camera Input Signal	Composite video signal 1 Vp-p 75Ω BNC, 4 Ch
Network Interface	Ethernet (10/100 Base-T)
Protocols	TCP/IP, ICMP, SMTP, HTTP, FTP
Main Monitor Output	Composite video signal 1 Vp-p 75Ω BNC
Call Monitor Output	Composite video signal 1 Vp-p 75Ω BNC
Audio input	4 audio inputs, (RCA)
Audio output	2 audio outputs, (RCA)
Motion Detect Area	15 * 12 for NTSC and 15 * 14 for PAL
Motion Detect Sensitivity	256 Levels
Video Loss Detection	Yes
Recording Rate	Up to 25 images/sec. for NTSC / 18 images/sec. for PAL
Picture in Picture	Yes (Movable)
Key Lock	Yes
Picture Zoom	2*2 (Movable)
Alarm Input	TTL input, Hi (5V), Low (GND)
Alarm Output	COM./N.O
Camera Title	6 letters
Video Adjustable	Color/ Contrast/ Brightness Adjustable
HDD	Not included